

# Olex MAX DPF DIESEL C3 5W-30

Superior sludge prevention to help extend engine life

Olex MAX DPF DIESEL C3 5W-30 is a gasoline and diesel engine oil that protects against the problems your engine faces.

Severe driving conditions can cause the buildup of a thick, tar-like substance called sludge. Sludge can block your engine's vital oil ways and if untreated it can rob an engine of power and, ultimately, its life. Olex MAX DPF DIESEL C3 5W-30 formula cleans away old sludge and protects against new sludge formation. Help extend the life of your engine with Olex Max DPF DIESEL C3 5W-30.

### Advantages

- Superior protection against viscosity and thermal breakdown.
- Low Speed Pre-Ignition (LSPI) prevention
- Excellent clean dispersion and provides effective lubrication.
- Provides superior protection against engine sludge.

### Applications

Olex MAX DPF DIESEL C3 5W-30 is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends an API SP, ACEA C3 Lubricant.

### Typical Characteristics

Name	Method	Unit	5W-30 c3
Density @ 15 °C	ASTM D1298	g/ml	0.852
Viscosity, Kinematic @ 100 °C	ASTM D445	mm <sup>2</sup> /s	11.19
Viscosity Index	ASTM D2270	-	165
Flash Point, COC	ASTM D92	°C	230
Pour Point	ASTM D97	°C	-36

\*The above test is a recent average and may vary within the range of maintaining performance.

### Product performance

- API SP.
- ACEA C3
- MB 229.31

### Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.