

OLEX Gasoline SL 10W-40

Protection to help extend engine life

OLEX Gasoline SL 10W-40 is essential maintenance of your engine by helping keep it clean and fighting wear. It is for use in service typical of gasoline engines in present and earlier passenger cars, sports utility vehicles, vans and light trucks operating under vehicle manufacturers recommended maintenance procedures.

Advantages

OLEX Gasoline SL 10W-40 provides;

- Cleaner engine on account of lower deposits in combustion chamber and exhaust
- Advanced protection against viscosity and thermal breakdown.
- Helps minimize oil consumption

Application

OLEX Gasoline SL 10W-40 is suitable for use in automotive gasoline engines where the manufacturer recommends an API SL or earlier specification 10W-40 lubricant.

Typical Characteristics

Name	Method	Unit	Olex SL 10W-40
Density @ 15 °C	ASTM D1298	g/cm ³	0.863
Kinematic Viscosity @ 40 °C	ASTM D445	mm ² /s	99.77
Kinematic Viscosity @ 100 °C	ASTM D445	mm ² /s	14.67
Viscosity Index	ASTM D2270	-	153
Pour Point	ASTM D97	°C	-39
Flash Point - COC	ASTM D92	°C	230
Total Base Number	ASTM D2896	mg KOH/g	8.5

*The above test is a recent average and may vary within the range of maintaining performance.

Product Performance:

API SL

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. Please refer to material safety data sheet.