

Olex SES SP 5W-30

Superior sludge prevention to help extend engine life

Olex SES SP 5W-30 is the premium engine oil for formulating Passenger Car suitable ILSAC GF-6 and API SP performance levels. Olex SES SP 5W-30 combats it's aging process and provides superior protection against harmful deposit build-up in higher mileage engines to help extend engine life.

Advantages

- Delivers fuel economy without compromising durability.
- Provides superior protection against engine sludge.
- Provides protection against Low Speed Pre Ignition and associated engine damage.
- Excellent clean dispersion and provides effective lubrication.

Applications

Olex SES SP 5W-30 is suitable for use in automotive gasoline engines where the manufacturer recommends an API SP, ILSAC GF-6 lubricant.

Typical Characteristics

Test items	Method (ASTM)	Unit	SAE 5W-30
Density @ 15 ℃	D1298		0.862
Viscosity, Kinematic @ 100 ℃	D445	mm²/s	10.2
Viscosity Index	D2270	-	155
Flash Point, COC	D92	°C	>220
Pour Point	D97	°C	-39

Product Performance

- API SP.
- ILSAC 6A

Storage

- Keep the products out of the direct rays of the sun.
- · Lay the drum down horizontally to prevent moisture from entering if store products at outside.
- Storage at room temperature. (keep under 60°C)